How to setup a cluster

What's a cluster???

There are two types of 'cl usters":

- Thightly coupled cluster ("real" cluster)
 - Latency of the interconnect is of main importance
 - Connected via InfiniBand, Myrinet or Quadrics
 - Mostly used for a single, common task ("massively parallel")
 - Identical setup of (almost) all machines in the cluster
- Loosely coupled cluster (f arm)
 - Latency is not important -> any interconnect possible
 - Applications on separate machines usually independent
 - Heterogeneous cluster very likely -> different setups

What do we have at CERN

The obvious answer is:

A very heterogeneous farm

- Off-the-shelf PCs (Dual-CPU)
- Several generations of machines
- Soon different architectures: x86, em64t (amd64)
- Different usages for a particular generation possible
- A few thousand boxes in the CC

Special machines

- Database servers (Oracle, Oracle RAC)
- Opencluster: Itanium architecture
- Standard boxes for special purposes

How do we setup/install the farm?

Very carefully ;-)

- Using standard tools
 - Kickstart and Netboot (TFTP/PXE)
 - RPMS reside on two servers (load balancing and failover)
- Custom tools -> QUATTOR
 - Template based configuration database
 - Automatic generation of kickstart-files
 - Central control of configuration(s)
- Private tools
 - Mainly scripts

How does it work??

With QUATTOR

- Create the templates
 - One per hardware configuration (rel. large)
 - One per box (small, mainly IP info)
 - Special info included as required
- Create the Kickstart file
- Install the box via kickstart/netboot
- Run the QUATTOR daemons
 - Upgrades; installation of additional software, etc.

Key Concepts of QUATTOR

Autonomous Nodes


• Local config files; No remote mgmt. scripts; Indep. of global FS (AFS, NFS)

Central Control


- Primary config file is kept centrally (and replicated on the nodes)
- Single source for all config files
- Reproducibility
- Scalability
 - Load balanced servers, Scalable protocols, etc.
- Use of public Standards
 - http(s), XML, rpm/pkg, SysV init scripts, etc.
- Portability
 - Any Linux distro, Solaris, other Unices, etc.

The Configuration

- Information is arranged in templates
- Common properties are stored only once
- Hierarchy of templates possible



Configuration Management



Configuration Database (CDB)

- x Keeps complete configuration information
- x Describes the *desired* state of the machines
- x Transaction mechanism enforces data consistency
- x Configurations are validated and under version control
- x Roll-back is possible!
- x Conflicts are detected

Examples of information in CDB

Hardware

- CPU, Hard disk, Network Card, Memory Size
- Location of the node in the CC
- System
 - Partition Table, Load Balancing information
- Cluster information
 - Cluster name and type, Batch master
- Software
 - Repository information, Service definition (group of rpms)
- Audit information
 - Contract type and number, Purchase date, etc.

Install Manager

- On top of standard vendor installer
 - OS version to install, Network and partition information
 - Which core packages, Custom post-install instructions
- Automated generation of Kickstart file
- Takes care of DHCP (TFTP/PXE) entries
- Available for RedHat Linux
 - Plugins for SuSE, Debian, Solaris, etc. possible

How does openlab do it??

Pre-QUATTOR

- Create Kickstart file by Hand
 - Special platform: supports two architectures (x86 + ia64)
 - Workarounds might be required
 - Relatively complex files
 - Assisted by a number of scripts
 - Current install procedure fits only this particular setup!!
 - ... but for this it's almost "perfect" ;-)
 - ullet It doesn't scale beyond $O(10^2)$ boxes
 - It doesn't scale beyond single admin

What about real clusters??

Specialized Linux distributions/tools

- Linux distribution for clusters: i.e. ROCKS
- Cluster tools on top of standard distros: i.e. OSCAR
- "Private" or vendor specific OS/Linux distro

Mostly very simple setup procedure

- Identical setup of all cluster machines
- Complications due to large number of boxes ($O(10^3)$)
- Possibility to use features of the interconnect (i.e. IB)